

DEWPOINT ANALYZER MODEL DP2000

SPECIFICATIONS

Measured Gas

Moisture Dew Point in exo or endo gas

Dewpoint Range

Standard Range: -50°F to +80°F. -46°C to +27°C

Display

LED Digital.

Resolution

+/- 0.1°F. Dew Point +/- 0.1°C

Accuracy and Repeatability

+/- 1°F. Dew Point +/- 1°C

Warm Up

Approximately 1 minute

Zero and Span Drift

+/- 1°F Dew Point MAX

Operating Temperature Range

0 to 120°F. -15°C to +49°C

Size and Weight

11"H x 10"W x 7"L . 8 Lbs

Power

115VAC 60Hz

Output

4-20mADC



Features

- Standard range of -50° F to +80° F
- Battery Operation. Truly Portable.
- Simple Operation
- Cell Temperature Readout
- Long Life dielectric ceramic sensor
- LED digital readout
- Built-in sample pump and filters
- No adjustments to make
- 4-20mADC output
- Manufactured by Super Systems, Inc.

McGoff-Bethune, Inc.

5970 Unity Dr. Suite A
Norcross, GA 30071
www.mcgoff-bethune.com

Phone 770-840-9811
FAX 770-840-7514
email bethune@mcgoff-bethune.com